



intimus CR-460 ECP

Electric creasing and
perforating machine



Durable creasing and perforating machine made of metal is well-suited for middle high runs in print shops, copy shops or bookbinders. A variety of blades are optional available for individual customer requirements.

2-in-1

Both creasing and perforating combined in one machine saves space and costs. Easy switch between creasing and perforating by changing the blade.

Precise

Measuring scale in mm and inches and flexible paper stops make sure the document has the correct position.

Easy-to-use

Operation either with electric foot pedal or by pushing a button.

Long-lasting

The core mechanism is protected by a metal cover



Article No.	INT-CR-0460ECP
Working width	460 mm
Creasing capacity	0.30-0.45 mm
Creasing width	1.6 mm
Creasing depth	0.5 mm
Perforating capacity	0.35 mm
Perforating width	1.4 mm
Perforating depth	0.7 mm
Noise level	50-55 dB (A)
Weight	42,3 kg
Dimensions (W x D x H)	710 x 540 x 245 mm
Power supply	220V, 50 Hz
Power consumption	150 W



intimus CR-460 ECP

Electric creasing and perforating machine



+ Full flexibility

For both creasing and perforating there are 5 different blade systems available suitable for every need. The machine comes standard with C46-B and P46-B.

CREASING BLADE SYSTEMS

Blade System	Working thickness	Blade thickness	Creasing width	Creasing depth
C46-A	< 0.36 mm	0.71 mm	1.3 mm	0.4 mm
C46-B	0.30 – 0.45 mm	0.71 mm	1.6 mm	0.5 mm
C46-C	0.40 – 0.50 mm	1.07 mm	1.7 mm	0.6 mm
C46-D	0.45 – 0.55 mm	1.07 mm	2.3 mm	0.7 mm
C46-E	0.50 – 0.65 mm	1.42 mm	2.7 mm	0.8 mm

PERFORATING BLADE SYSTEMS

Blade System	Working thickness	Teeth per inch	Perforating width	Perforating depth
P46-A	< 0.30 mm	16:1	0.8 mm	0.8 mm
P46-B	< 0.35 mm	12:1	1.4 mm	0.7 mm
P46-C	< 0.40 mm	10:1	1.2 mm	1.2 mm
P46-D	< 0.45 mm	8:1	2.0 mm	1.0 mm
P46-E	< 0.50 mm	6:1	3.0 mm	1.0 mm