BLUECREST™

Vantage® Mail Sorting Machine

Optimize your letter processing efficiency.

The Vantage mail sorting machine is powered by BlueCrest Business Logic Processing and Postal SortEngine™ software. Featuring FlexLine™ stackers, the system combines speed, intelligence and endurance. It provides the highest overall operational throughput and integrity in the industry, with speeds up to 45K/hr.

Improve sorting consistency and reduce downtime by:

- Tracking individual mail pieces throughout
- Eliminating the possibility of doubles and rework
- Capitalizing on mail processing efficiency and revenue

For more information, visit us online: bluecrestinc.com

Standard operating features:

- Large 92" auto feed deck
- Variable speed control
- Enhanced mail settling section
- Mail piece static guard
- Flexible tier pockets: positive piece level tracking
- Intuitive graphical user interface
- Standard/Info Mail support
- One button self-test
- PBMC operational reporting package

Options:

- WABCR (Wide Area Barcode Reading)
- MLOCR with handwriting capabilities
- Inbound/outbound processing
- Separator card detection
- Double-detector
- Selective mail piece opener
- Dual lane inline weigh-on-the-fly scale
- Local video encoding
- MERLIN® standards grading verification
- FlexLine™ Multiple Tier Stackers
- Single or double-side stackers
- Intelligent Mail® Full Service
- Track and trace integration
- Mail piece image archival
- Helpdesk on-call on-site service
- In-line metering

Notable features

- Postal SortEngine™ software
- Remote SiteVue™ diagnostic tool
- Three dimensional measurement
- Backside mail image capture
- Stacker section LED displays
- System overhead marquee

Specifications	Letters only	Letters and flats
Length, minimum	5.0"	6.0"
Length, maximum	11.25"	13.00"
Height, minimum	3.50"	3.50"
Height, maximum	7.50"	10.00"
Thickness, minimum	.007"	. 007"
Thickness, maximum	. 25"	.25"
Weight, minimum	.07oz	.07oz
Weight, maximum	4.0oz	8.8oz
Design speed for #10/HR	50K	40K
Postcard design speed/HR	50K	40K
Flats design speed/HR	NA	24K
Standard feeder magazine capacity	92"	92"
Pockets, maximum	>1000	160
Pockets, minimum	24/12	8
Stacker tier levels	4, 3, or 2 tier levels	1 tier level
Stacker pockets, minimum	Single-side: 24/18/12 Double-side: 48/36/24	8V

BlueCrest Inc. / 37 Executive Drive / Danbury, CT 06810

For more information, call 877-406-7704 or visit us online at bluecrestinc.com.